NEWgenerator[™]: Field Tests of an Off-grid Non-Sewered Sanitation System for Developing Countries and Remote Locations

Robert Bair, PhD

C. Castro, H.Y. Shyu, L. Xaba, D.H. Yeh

University of South Florida & University of KwaZulu-Natal









Water Sanitation & Hygiene Research & Development Centre

Disclaimer:

The materials being presented represent the speaker's own opinions and do NOT reflect the opinions of NOWRA.

Informal Housing Settlements

- Approx. 1 billion people
- High density and land value
- Low infrastructure coverage



د https://en.wiktionary.org/wiki/slum#/media/File:Mumbai_03-2016_108_Bandra_station_surroundings.jpg

Informal Settlement Sanitation

- Dependence on communal toilets
- High failure rates of traditional sanitation technologies
 - Septic tanks, pit latrines

The Need

- Compact & high efficiency treatment is needed
- Ability to recycle water
- Off-grid operation



Technology Selection

Anaerobic digestion:

• Pros:

Low energy requirements Provides energy source Can treat high COD conc.



• Cons:

Large reactor size

Susceptible to microbial washout

Poor effluent quality



Anaerobic membrane bioreactor (AnMBR)

Hybrid Process: Anaerobic Digestion + Membrane Filtration



Benefits

- Smaller AD systems
- Safely removes pathogens
- Consistent effluent quality
- No microbial washout

Nutrient Capture & Polishing

Z1

- AD is good at releasing nutrients not removing them
- IX can passively remove NH4+
- Independent of loading rate
- High removal rates
- GAC for final polishing



Disinfection

- Chlorine residual in treated water
- Limit the amount of chlorine stored onsite
- Onsite chlorine generation
- Electrolytic cell = electricity + salt



The NEWgenerator



Containerized

Off-grid Operation

Autonomous



NEWgenerator History



Field Validation – Southern India – 1 Year



Community Ablution Blocks (sanitation + hygiene facilities)



Durban Field Trial: Unit



Durban Field Trial: Test Plan



Results: Chemical Oxygen Demand



Stage A Stage B Stage C

- · ISO30500 Category A

Results: TSS



- · ISO30500 Category A



- · ISO30500 Category A

Results: Pathogens & Indicator Species



- E.coli always below detection limits in final water
- No helminths detected in final effluent
- Membrane filtration primary mechanism for pathogen rejection



Non-sewered sanitation systems

ISO 30500: Liquid Effluent Criteria

Parameter	Criteria	Meet?
TSS	< 30 mg/L	YES
COD	< 150 mg/L	YES
рН	6-9	YES
TN	>70% removal	YES (current R&D to reduce OPEX)
ТР	>80% removal	Partial (removing 40%, current R&D underway to meet)
Pathogen: Bacterial	<100/L (>6LRV)	YES
Pathogen: Helminth	<1/L (>4LRV)	YES
Pathogen: Virus	<10/L (>7LRV)	Anticipate yes (not yet tested, requires surrogate spiking)
Pathogen: Protozoan	<1/L (>6LRV)	Anticipate yes (not yet tested, requires surrogate spiking)

Conclusions

- AnMBRs can successfully be implemented in informal settlements
- NCS is able to passively remove TN High removal rates
- Field regeneration of the NCS was able to restore its sorption capacity
- NEWgenerator can meet most of the ISO 30500 NSSS requirements





Shyu, H.Y., et al (2021) The NEWgenerator non-sewered sanitation system: Long-term field testing at an informal settlement community in eThekwini municipality, South Africa. Journal of Environ. Management.



Castro, C.J., et al (2021) Performance and onsite regeneration of natural zeolite for ammonium removal in a field-scale non-sewered sanitation system. Sci. of the total Environ.





NEWgenerator[™] *nutrients* • *energy* • *water*



www.membiolab.com



Robert Bair rbair@usf.edu